

PRODUCT SAFETY DATA SHEET



HEALTH · HYGIENE · HOME

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

AIR WICK Freshmatic Max Crisp Linen & Lilac

1.2. Relevant identified uses of the substance or mixture and uses advised against

For fragrancing and ambience / mood creation

1.3. Details of the Supplier of the Safety Data Sheet

The United Kingdom:

RB UK Commercial Ltd
Wellcroft House
Wellcroft Road
Slough
Berkshire
SL1 4AQ

The Republic Of Ireland:

Reckitt Benckiser Ireland Ltd
7 Riverwalk
Citywest Business Campus
Dublin 24
Ireland

1.4 Emergency telephone number

RB UK Contact Telephone: 0845 769 7079 **RB ROI Contact Telephone:** 01 661 7318

Only available during the following office hours: 09:00 - 17:00 weekdays

RB Contact Email: consumer.relations-ukroi@rb.com

Poisons Information Centre of Ireland: 01 809 2166 8am-10pm 7 days a week

| Revision Date: | Revision | Replacing |
|-----------------|----------|------------------------|
| 1 February 2017 | 6 | 0125638105 01 Dec 2014 |

RB Ref No:
0125638106

Revisions: Updated data sheet, multiple changes

Additional useful information

Product Format: Aerosol can in plastic sleeve with plastic device



UN Transport Code UN: 1950
Class & Packing Group 2.1
Proper Shipping Name Aerosols
Store below 50°C

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word : Danger

Hazard statements : Extremely flammable aerosol.
Pressurised container: May burst if heated.

Precautionary statements

- General** : Keep out of reach of children.
If medical advice is needed, have product container or label at hand.
Use only as directed
- Prevention** : Pressurised container: May burst if heated.
Protect from sunlight and do not expose to temperatures exceeding 50 °C.
Do not pierce or burn, even after use.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking
Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.
- Response** : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Storage** : Not applicable.
- Disposal** : Not applicable.
- Supplemental label elements** : Contains 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone, p-t-Butyl-alpha-methylhydrocinnamic aldehyde and alpha-Hexylcinnamaldehyde.
May produce an allergic reaction. Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

2.3 Other hazards

Other hazards which do not result in classification : None known.

Recommendations : People suffering from perfume sensitivity should be cautious when using this product.
Air Fresheners do not replace good hvac practices.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures : Mixture

| Product/ingredient name | Identifiers | % | Regulation (EC) No. 1272/2008 [CLP] | Type |
|---|--|-----------|---|---------|
| ethanol | REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5 | ≥25 - ≤50 | Flam. Liq. 2, H225 | [2] |
| Butane | REACH #: 01-2119474691-32 EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0 | ≥25 - ≤50 | Flam. Gas 1, H220 Press. Gas Comp. Gas, H280 | [2] |
| isobutane | REACH #: 01-2119485395-27 EC: 200-857-2 CAS: 75-28-5 Index: 601-004-00-0 | ≥10 - ≤25 | Flam. Gas 1, H220 Press. Gas Comp. Gas, H280 | [2] |
| propane | REACH #: 01-2119486944-21 EC: 200-827-9 CAS: 74-98-6 Index: 601-003-00-5 | ≥10 - ≤25 | Flam. Gas 1, H220 Press. Gas Comp. Gas, H280 | [2] |
| methanol | REACH #: 01-2119392409-28 EC: 200-659-6 CAS: 67-56-1 Index: 603-001-00-X | <3 | Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 1, H370 | [1] [2] |
| 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl) ethanone | EC: 259-174-3 CAS: 54464-57-2 | <0.25 | Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 1, H410 (M=1) | [1] |
| p-t-Butyl-alpha-methylhydrocinnamic aldehyde | REACH #: 01-2119485965-18 EC: 201-289-8 CAS: 80-54-6 | ≤0.3 | Acute Tox. 4, H302 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361fd (Fertility and Unborn child) Aquatic Chronic 2, H411 | [1] |
| alpha-Hexylcinnamaldehyde | EC: 202-983-3 CAS: 101-86-0 | ≤0.3 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411 See Section 16 for the full text of the H statements declared above. | [1] |



There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: HANDLING AND STORAGE

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

Seveso Directive - Reporting thresholds (in tonnes)

Named substances

| Name | Notification and MAPP threshold | Safety report threshold |
|--|---------------------------------|-------------------------|
| Methanol | 500 | 5000 |
| Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas | 50 | 200 |
| Liquefied extremely flammable gases (including LPG) and natural gas | 50 | 200 |

Danger criteria

| Category | Notification and MAPP threshold | Safety report threshold |
|--|---------------------------------|-------------------------|
| 3a: Flammable aerosols containing flammable gases or flammable liquids | 150 | 500 |

7.3 Specific end use(s)

- Recommendations** : Air care products
Consumer uses

- Industrial sector specific solutions** : Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

| Product/ingredient name | Exposure limit values |
|-------------------------|--|
| Ethanol | EU OEL (Europe, 12/2011). TWA: 1000 ppm 8 hours. |
| Butane | EU OEL (Europe, 7/2012). Notes: Ministry of Labour (Brochure INRS Ed 984, July 2012). Indicative exposure limits TWA: 800 ppm 8 hours. |
| isobutane | EU OEL (Europe, 1/2012). TWA: 1900 mg/m ³ 8 hours. |
| propane | EU OEL (Europe, 5/2010). Oxygen Depletion [Asphyxiant]. OELV-8hr: 1000 ppm 8 hours. |
| methanol | EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 200 ppm 8 hours. TWA: 260 mg/m ³ 8 hours. |

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

| Product/ingredient name | Type | Exposure | Value | Population | Effects |
|-------------------------|------|----------------------|-----------------------|------------|----------|
| Methanol | DNEL | Long term Inhalation | 260 mg/m ³ | Workers | Systemic |
| | DNEL | Long term Dermal | 40 mg/kg bw/day | Workers | Systemic |
| | DNEL | Long term Inhalation | 50 mg/m ³ | Consumers | Systemic |
| | DNEL | Long term Dermal | 8 mg/kg bw/day | Consumers | Systemic |
| | DNEL | Long term Oral | 8 mg/kg bw/day | Consumers | Systemic |

PNECs

| Product/ingredient name | Compartment Detail | Value | Method Detail |
|-------------------------|------------------------|---------------|--------------------------|
| Methanol | Fresh water | 20.8 mg/l | Assessment Factors |
| | Marine water | 2.08 mg/l | Assessment Factors |
| | Sewage Treatment Plant | 100 mg/l | Assessment Factors |
| | Fresh water sediment | 77 mg/kg dwt | Equilibrium Partitioning |
| | Marine water sediment | 7.7 mg/kg dwt | Equilibrium Partitioning |
| | Soil | 100 mg/kg dwt | Equilibrium Partitioning |

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

| | |
|--|---------------------------|
| Physical state | : Liquid. [Aerosol.] |
| Colour | : Colourless. |
| Odour | : Characteristic. |
| Odour threshold | : Not available. |
| pH | : Not available. |
| Melting point/freezing point | : Not available. |
| Initial boiling point and boiling range | : <34°C |
| Flash point | : Closed cup: <0°C |
| Evaporation rate | : Not available. |
| Flammability (solid, gas) | : Not available. |
| Burning time | : Not applicable. |
| Burning rate | : Not applicable. |
| Upper/lower flammability or explosive limits | : Not available. |
| Vapour pressure | : Not available. |
| Vapour density | : Not available. |
| Density | : 0.639 g/cm ³ |
| Solubility(ies) | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Decomposition temperature | : Not available. |
| Viscosity | : Not available. |
| Explosive properties | : Not available. |
| Oxidising properties | : Not available. |
| Corrosivity Remarks | : Not available. |

9.2 Other information

| | |
|---------------------|--|
| Solubility in water | : <input checked="" type="checkbox"/> Not available. |
| Type of aerosol | : Spray |
| Heat of combustion | : <input checked="" type="checkbox"/> 5.18 kJ/g |

No additional information.

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).
- 10.5 Incompatible materials** : No specific data.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Instability Conditions** : Not available.
- Instability temperature** : Not available.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--|------------------------|---------|--------------------------|----------|
| ethanol | LC50 Inhalation Vapour | Rat | 124700 mg/m ³ | 4 hours |
| | LD50 Oral | Rat | 7 g/kg | - |
| butane | LC50 Inhalation Vapour | Rat | 658000 mg/m ³ | 4 hours |
| isobutane | LC50 Inhalation Vapour | Rat | 658000 mg/m ³ | 4 hours |
| methanol | LC50 Inhalation Gas. | Rat | 145000 ppm | 1 hours |
| | LC50 Inhalation Gas. | Rat | 64000 ppm | 4 hours |
| 2-(4-tert-butylbenzyl) propionaldehyde | LD50 Dermal | Rabbit | 15800 mg/kg | - |
| | LD50 Oral | Rat | 5600 mg/kg | - |
| | LD50 Dermal | Rabbit | >5000 mg/kg | - |
| α-hexylcinnamaldehyde | LD50 Oral | Rat | 1390 mg/kg | - |
| | LD50 Oral | Rat | 3100 mg/kg | - |

Acute toxicity estimates

| Route | ATE value |
|----------------------|---------------|
| Oral | 5702.3 mg/kg |
| Dermal | 17106.9 mg/kg |
| Inhalation (vapours) | 171.1 mg/l |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---|--------------------------|------------|-------|-------------------------|-------------|
| ethanol | Eyes - Moderate irritant | Rabbit | - | 0.06666667 minutes | - |
| | Eyes - Mild irritant | Rabbit | - | 100 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Eyes - Severe irritant | Rabbit | - | 100 microliters | - |
| | Skin - Mild irritant | Rabbit | - | 500 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 400 milligrams | - |
| methanol | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Eyes - Moderate irritant | Rabbit | - | 100 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 40 milligrams | - |
| 2-(4-tert-butylbenzyl) propionaldehyde α-hexylcinnamaldehyde | Skin - Moderate irritant | Rabbit | - | 24 hours 20 milligrams | - |
| | Skin - Severe irritant | Guinea pig | - | 24 hours 500 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 100 milligrams | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 500 milligrams | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 100 milligrams | - |

Sensitisation

No known effect according to our database.

Mutagenicity

No known effect according to our database.

Carcinogenicity

No known effect according to our database.

Reproductive toxicity

No known effect according to our database.

Teratogenicity

No known effect according to our database.

Specific target organ toxicity (single exposure)

| Product/ingredient name | Category | Route of exposure | Target organs |
|-------------------------|------------|-------------------|----------------|
| methanol | Category 1 | Not determined | Not determined |

Specific target organ toxicity (repeated exposure)

No known effect according to our database.

Aspiration hazard

No known effect according to our database.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|--|----------|
| ethanol | Acute EC50 17.921 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute EC50 2000 µg/l Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 25500 µg/l Marine water | Crustaceans - Artemia franciscana - Larvae | 48 hours |
| | Acute LC50 42000 µg/l Fresh water | Fish - Oncorhynchus mykiss | 4 days |
| | Chronic NOEC 4.995 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Chronic NOEC 0.375 ul/L Fresh water | Fish - Gambusia holbrooki - Larvae | 12 weeks |
| methanol | Acute EC50 16.912 mg/l Marine water | Algae - Ulva pertusa | 96 hours |
| | Acute LC50 2500000 µg/l Marine water | Crustaceans - Crangon crangon - Adult | 48 hours |
| | Acute LC50 3289 mg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 290 mg/l Fresh water | Fish - Danio rerio - Egg | 96 hours |
| | Chronic NOEC 9.96 mg/l Marine water | Algae - Ulva pertusa | 96 hours |

12.2 Persistence and degradability

No known effect according to our database.

12.3 Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|---------------------------------------|--------------------|-------|-----------|
| ethanol | -0.35 | - | low |
| butane | 2.89 | - | low |
| isobutane | 2.8 | - | low |
| propane | 1.09 | - | low |
| methanol | -0.77 | <10 | low |
| 2-(4-tert-butylbenzyl)propionaldehyde | 4.2 | 349.8 | low |

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.





Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

SECTION 14: TRANSPORT INFORMATION

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

| | ADR/RID | ADN | IMDG | IATA |
|--|--|--|---|--|
| 14.1 UN number | UN1950 | UN1950 | UN1950 | UN1950 |
| 14.2 UN proper shipping name | AEROSOLS | AEROSOLS | <input checked="" type="checkbox"/> AEROSOLS. Marine pollutant (ethanol) | Aerosols, flammable |
| 14.3 Transport hazard class(es) | 2  | 2  | 2.1  | 2.1  |
| 14.4 Packing group | - | - | - | - |
| 14.5 Environmental hazards | No. | No. | <input checked="" type="checkbox"/> Yes. | <input checked="" type="checkbox"/> Yes. The environmentally hazardous substance mark is not required. |
| Additional information | Limited quantity | Limited quantity | Limited quantity | See DG List |

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable.
**on the manufacture,
 placing on the market
 and use of certain
 dangerous substances,
 mixtures and articles**

Other EU regulations

Europe inventory : Not determined.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Aerosol dispensers :

3



Extremely flammable

Seveso Directive

This product is controlled under the Seveso Directive.

Named substances

| Name |
|---|
| <input checked="" type="checkbox"/> Methanol Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas Liquefied extremely flammable gases (including LPG) and natural gas |

Danger criteria

| Category |
|--|
| <input checked="" type="checkbox"/> 3a: Flammable aerosols containing flammable gases or flammable liquids |

Hazard class for water : 1 Appendix No. 4

15.2 Chemical safety assessment : Not applicable.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms

- : ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification | Justification |
|-----------------------|-----------------|
| Aerosol 1, H222, H229 | Expert judgment |

Full text of abbreviated H statements

| | |
|--|---|
| <p>H220 H222, H229</p> <p>H225 H280 H301 H302 H311 H315 H317 H319 H331 H361fd</p> <p>H370 H400 H410 H411</p> | <p>Extremely flammable gas. Extremely flammable aerosol. Pressurised container: May burst if heated.</p> <p>Highly flammable liquid and vapour. Contains gas under pressure; may explode if heated.</p> <p>Toxic if swallowed. Harmful if swallowed.</p> <p>Toxic in contact with skin. Causes skin irritation.</p> <p>May cause an allergic skin reaction. Causes serious eye irritation.</p> <p>Toxic if inhaled. Suspected of damaging fertility. Suspected of damaging the unborn child.</p> <p>Causes damage to organs. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.</p> |
|--|---|

Full text of classifications [CLP/GHS]

| | |
|---|---|
| <p>Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Acute Tox. 4, H302 Aerosol 1, H222, H229 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 2, H411 Eye Irrit. 2, H319 Flam. Gas 1, H220 Flam. Liq. 2, H225 Press. Gas Comp. Gas, H280 Repr. 2, H361fd</p> <p>Skin Irrit. 2, H315 Skin Sens. 1, H317 Skin Sens. 1B, H317 STOT SE 1, H370</p> | <p>ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 ACUTE TOXICITY (oral) - Category 4 AEROSOLS - Category 1 ACUTE AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 FLAMMABLE GASES - Category 1 FLAMMABLE LIQUIDS - Category 2 GASES UNDER PRESSURE - Compressed gas REPRODUCTIVE TOXICITY (Fertility and Unborn child) - Category 2 SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 1</p> |
|---|---|

This document complements the technical usage instructions but does not replace them. The information contained herein is based on our best current knowledge of the product concerned, and is given in good faith. The attention of recipients is drawn to (amongst other things) the element of risk consequent to use of the product other than that for which it was intended.

In no way does this document remove the need of the recipient of the product to fully understand and apply statutory requirements. It is the recipient's sole responsibility to take due precautions relative to the use made of the product. All information contained herein is only to assist the recipient in fulfilling their statutory duty connected with the use of hazardous materials.

This Document may be entitled Product Safety Data Sheet as required by REACH (Registration, Evaluation, Authorisation and restriction of Chemicals) Annex II OR Product Data Information Sheet where a product is not required to be supported by a full REACH compliant SDS (e.g. not classified as hazardous or out of scope, such as cosmetics). Changes from the previous version are given in Section 1.

This list of information must not be considered as exhaustive, and does not exonerate the recipient from taking other precautions described in documents other than those mentioned, concerning the storage and use of the product, for which they remain the sole person responsible.